FORM	PTO-139	90 (Modified) U.S. DEPARTMENT	OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER				
	- 17	RANSMITTAL LETTER	TO THE UNITED STATES	KSN0026				
	DESIGNATED/ELECTED OFFICE (DO/EO/US)  U.S. APPLICATION NO. (IF KNOWN, SEE 37)							
	CONCERNING A FILING UNDER 35 U.S.C. 371 10/049947							
DITE	DNIAT	IONAL APPLICATION NO	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED				
INTE		PCT/IB00/01377	21 August 2000	20 August 1999				
		NVENTION NENT FOR ASSEMBLY ON	A PRINTED CIRCUIT BOARD	1				
CON	MPO	NENT FOR ASSEMBLY ON	A PRINTED CIRCUIT BOARD	,				
A DDI	ICAN'	T(S) FOR DO/EO/US						
		inbesien						
Appli	icant l	nerewith submits to the United Sta	tes Designated/Elected Office (DO/EO/US) the	e following items and other information:				
1.	×	This is a <b>FIRST</b> submission of it	tems concerning a filing under 35 U.S.C. 371.					
2.			UENT submission of items concerning a filing	g under 35 U.S.C. 371.				
3.		This is an express request to beg	<del>-</del>	371(f)). The submission must include itens (5), (6),				
3		(9) and (24) indicated below.						
4.	$\boxtimes$	· · · · · · · · · · · · · · · · · · ·	expiration of 19 months from the priority date	(Article 31).				
5.	$\boxtimes$		ication as filed (35 U.S.C. 371 (c) (2))					
		· ·	ired only if not communicated by the Internat	ional Bureau).				
			by the International Bureau.					
_	521		pplication was filed in the United States Recei					
6.	×		of the International Application as filed (35 U.	.S.C. 371(c)(2)).				
		a. 🛛 is attached hereto.						
7			omitted under 35 U.S.C. 154(d)(4).	10 (25 H S C 271 (a)(2))				
7.			International Application under PCT Article juired only if not communicated by the Interna					
		· ·	ed by the International Bureau.	nonai Bureau).				
			owever, the time limit for making such amenda	nents has NOT expired				
		d. have not been made and		nents has tvo r expired.				
8.			of the amendments to the claims under PCT A	rticle 19 (35 U.S.C. 371(c)(3)).				
9.		An oath or declaration of the inv		· · · · · · · · · · · · · · · · · · ·				
10.	×	An English language translation Article 36 (35 U.S.C. 371 (c)(5))	of the annexes to the International Preliminary	Examination Report under PCT				
11.	$\boxtimes$	A copy of the International Preli	minary Examination Report (PCT/IPEA/409).					
12.	$\boxtimes$	A copy of the International Search	ch Report (PCT/ISA/210).					
It	tems 1	13 to 20 below concern document	c(s) or information included:					
13.		An Information Disclosure State	ement under 37 CFR 1.97 and 1.98.					
14.		An assignment document for rec	ording. A separate cover sheet in compliance	with 37 CFR 3.28 and 3.31 is included.				
15.	$\boxtimes$	A FIRST preliminary amendment	nt.					
16.		A SECOND or SUBSEQUENT	preliminary amendment.					
17.		A substitute specification.						
18.		A change of power of attorney as						
19.			sequence listing in accordance with PCT Rule					
20.		• •	international application under 35 U.S.C. 154(					
21.			aguage translation of the international application	on under 35 U.S.C. 154(d)(4).				
22. 23.	⊠ ⊠	Certificate of Mailing by Express	S IVIAII					
23.		Other items or information:						
	Check No. 100436							
			<b>.</b>					

. I JOIORectifully 1 9 FEB 2002

U.S. Al	S. APPLICATION NO (IE KNOWN SEE 37 CFR INTERNATIONAL APPLICATION NO PCT/IB00/01377				ATTORNEY'S DOCKET NUMBER  KSN0026							
<i>2</i> 4.	The following fees are submitted:.					CALCULATIONS	S PTO USE ON	NLY				
	BASIC NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5)):  Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO											
<ul> <li>✓ International preliminary examination fee (37 CFR 1.482) not paid to</li> <li>USPTO but International Search Report prepared by the EPO or JPO</li></ul>												
	Internation but int	tional ernatio	preliminary examin onal search fee (37 C	ation fee (37 CFR 1.445(a)	CFR 1.482) not paid t (2)) paid to USPTO	o USPTC	) 	\$740.	00			
	but all	claims	did not satisfy prov	isions of PC	CFR 1.482) paid to Ut T Article 33(1)-(4)			\$710.	00			
	Interna and all	tional claim	s satisfied provision	s of PCT Art	CFR 1.482) paid to Uticle 33(1)-(4)			\$100.	00			
					ATE BASIC FE				_	\$890.00		
			0 for furnishing the iest claimed priority	date (37 Cl	FR 1.492 (e)).	□ 20	0	□ 30		\$0.00		
CL	AIMS		NUMBER I	FILED	NUMBER EXT	RA		RATE				
Total c	laims		20	- 20 =	0		х	\$18.00		\$0.00		
	ndent c		2	- 3=	0		х	\$84.00	_	\$0.00	-	
Multip	le Depe	endent	Claims (check if ap		A BOYE CALC	NTIT ACT		NG		\$0.00		
	1.				ABOVE CALC				=	\$890.00		
	pplicar			s. See 37 CF	R 1.27). The fees indic					\$0.00		
						SUB'	<u> </u>	ΓAL :	=	\$890.00		
			30.00 for furnishing liest claimed priority		translation later than FR 1.492 (f)).	□ 20	0	□ 30	+	\$0.00		
		****			TOTAL NAT	IONAI	L FI	EE	=	\$890.00		
Fee for	record	ing the	e enclosed assignme appropriate cover sh	nt (37 CFR 1 eet (37 CFR	1.21(h)). The assignme 3.28, 3.31) (check if a	nt must b	e).			\$0.00		
					TOTAL FEES	ENCL	OS	ED	=	\$890.00		
										Amount to be: refunded	\$	
										charged	\$	
a.	×	A ch	eck in the amount o	f \$890	0.00 to cover the	above fee	s is e	nclosed.	•			
b.			se charge my Deposi plicate copy of this			in the am	ount	of		to cover the	he above fees.	
c.	$\boxtimes$		Commissioner is her	reby authoriz	ed to charge any additi A duplicate cor			-		uired, or credit any o	overpayment	
d.					d. WARNING: Inform			-		-		
NOTE	: Whe	re an	appropriate time li	mit under 3'	7 CFR 1.494 or 1.495 re the application to p	has not b	een i	met, a pe	titio	nfto revive (37 CFR	t .	
```	,	,,			e the application to p	chaing s	.a.u.s.			H ~		
SEND	ALL C	ORRE	SPONDENCE TO:			l			X	1' Colu		
	J. Groe						SI	GNATU	E/			
Baker & Daniels 205 West Jefferson Blvd.				n. hal								
Suite 250				Eric/J. Green NAME								
South	Bend,	IN 46	601					1 /	,			
Telen	hone:	574-23	34-4149					2,230				
_	Fax: 574-239-1900				REGISTRATION NUMBER							
							Fe	ebruary	19,	2002		
							$\overline{\mathbf{D}}_{\ell}$	ATE				

#### IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant(s):

Johan Vanbesien

Filed:

PCT/IB00/01377 (August 21, 2000)

Serial No.:

COMPONENT FOR ASSEMBLY ON A PRINTED

Title:

**CIRCUIT BOARD** 

Group/Art Unit:

Examiner:

Docket No.:

KSN0026

Honorable Commissioner for Patents Washington, D.C. 20231

Sir:

#### PRELIMINARY AMENDMENT

In the above-mentioned PCT application, please accept the enclosed application under the national stage pursuant to 35 USC § 371 and amend the application as follows:

## In the Claims:

Please replace claims 1-6 of the application with claims 1-20 as follows:

1. An electrical connector for mounting on a printed circuit board, comprising a multiplicity of electrical terminal members to be connected to said circuit board and being in the form of a matrix including a plurality of rows and columns each, wherein several terminal member groups, each comprising several terminal members in the form of SMT contacts to be soldered to the circuit board, are fixed in a predetermined relative position independently of each other by plastic bodies of their own that are injection-molded thereto, several plastic bodies along with the terminal member groups extending through the same are adapted to be fixed in predetermined relative positions, and the plastic bodies fixed in a predetermined relative position, along with the terminal member groups extending through the same, are movable perpendicularly to the circuit board surface independently of each other.

SBIMAN1 116300v2 -1-

2. A connector according to claim 1, wherein the plastics body along with the terminal members extending through the same is movable relative to specific or all remaining constituent parts of the connector.

I

乙.

- 3. A connector according to claim 1, wherein the terminal members of the terminal member groups each are such terminal members that are manufactured in common.
- 4. A connector according to claim 1, wherein the terminal members of the terminal member groups each are such terminal members that can be connected to the circuit board at mutually adjacent locations.
- 5. A connector according to claim 1, wherein the several plastics bodies along with the terminal member groups extending through the same are movable relative to each other.
- 6. A connector according to claim 1, wherein the terminal members extending through the respective plastics bodies are the sole constituent parts each of the connector to which the plastics bodies are connected.
- 7. A connector according to claim 5, wherein the plastic bodies include alignment members molded within the plastic body.
- 8. A connector according to claim 7, wherein the connector includes an outer housing having a plurality of spaced apart walls arranged in columns, said plastic bodies and said spaced apart walls having cooperating alignment members.
- 9. A connector according to claim 8, wherein said alignment members comprise cooperating grooves and ribs.
- 10. A connector according to claim 9, wherein said cooperating grooves and ribs are vertically extending.
- 11. An electrical connector for mounting on a printed circuit board, comprising a plurality of electrical terminal members profiled for connection to the circuit board and being in the form of a matrix including a plurality of rows and columns, wherein several terminal member groups, each comprising several terminal members in the form of contacts to be soldered to the circuit board, are fixed in a predetermined relative position independently of each other by molded plastic bodies, several molded plastic bodies along with the terminal member groups extending through the same are adapted to be fixed in predetermined relative positions, and the molded plastic bodies, along with the terminal member groups extending

through the same, are movable perpendicularly to the circuit board surface independently of each other.

- 12. A connector according to claim 7, wherein the plastic body along with the terminal members extending through the same is movable relative to specific or all remaining constituent parts of the connector.
- 13. A connector according to claim 7, wherein the terminal members of the terminal member groups each are such terminal members that are manufactured in common.
- 14. A connector according to claim 7, wherein the terminal members of the terminal member groups each are such terminal members that can be connected to the circuit board at mutually adjacent locations.
- 15. A connector according to claim 7, wherein the several plastics bodies along with the terminal member groups extending through the same are movable relative to each other.
- 16. A connector according to claim 7, wherein the terminal members extending through the respective plastic bodies are the sole constituent parts each of the connector to which the plastics bodies are connected.
- 17. A connector according to claim 14, wherein the plastic bodies include alignment members molded within the plastic body.
- 18. A connector according to claim 16, wherein the connector includes an outer housing having a plurality of spaced apart walls arranged in columns, said plastic bodies and said spaced apart walls having cooperating alignment members.
- 19. A connector according to claim 16, wherein said alignment members comprise cooperating grooves and ribs.
- 20. A connector according to claim 19, wherein said cooperating grooves and ribs are vertically extending.

Z. .

# **REMARKS**

Applicant respectfully requests that the above preliminary amendment be entered, and that the fees due herewith are calculated using the new claims, not the claims of the PCT application.

Respectfully submitted,

Eric J. Groon, Reg. No. 32,230

BAKER & PANIELS

205 West Jefferson Blvd., Suite 250 South Bend, IN 46601

Tel: (574) 234-4149

Fax: (574)239-1900

جر ، ،

3/PATS

10/049947 JC10 Rec'd PCT/PTO 1 9 FEB 2002

1/14

(PCT/IB00/01377)

#### Description

### Component for Mounting on a Printed Circuit Board

The present invention relates to a device according to the generic clause of claim 1, i.e. to a component for mounting on a printed circuit board, comprising a multiplicity of electrical terminal members for connection to the circuit board.

Such a component is, for example, the electrical connector shown in Fig. 5. The electrical connector shown consists in essence of contact elements, not shown in Fig. 5, for connecting the electrical connector to another electrical connector, a housing 1 enclosing the contact elements, electrical terminal members 2 extending out of housing 1 for soldering the electrical connector to a printed circuit board LP, and an alignment plate 3.

By means of the alignment plate 3, the electrical terminal members 2 of the electrical connector are held in a predetermined relative position. As regards further details of alignment plate 3, reference is made to document DE 197 54 877 A1.

Holding of the electrical terminal members in a predetermined relative position is of advantage in particular when the electrical connector is a component for surface mounting, i.e. when the electrical terminal members are so-called SMT contacts.

SMT contacts are designed to be soldered to surface contacts of the printed circuit board. In this regard, soldering paste is applied first to the surface contacts of the circuit board, thereafter the component to be soldered to the circuit board is arranged on the circuit board, and finally the soldering operation proper takes place by heating the locations concerned.

For performing proper soldering, the locations of the electrical terminal members of the electrical connector to be soldered to the surface contacts of the circuit board must be in contact with the soldering paste during heating; otherwise, a solder connection obviously cannot be established between the surface contacts of the circuit board and the electrical terminal members of the electrical connector.

45

50

65

For this reason, the locations to be soldered of the electrical terminal members of a component have to be located approximately in one plane. Possibly existing deviations from a coplanar arrangement of these locations are tolerable to a very limited extent only.

This is a serious problem in particular with components having a very large number of electrical terminal members.

For eliminating this problem, the electrical terminal members of surface-mountable components are not seldom fixed in their proper relative position by the aforementioned alignment plate 3. The effect achievable thereby is that the locations to be soldered of all electrical terminal members are located in one plane.

70 That the electrical terminal members of a component assume an exactly prescribed relative position may also be necessary for components that are not designed for sur-

face mounting. In this case, too, the use of an alignment plate or the like may turn out to be advantageous.

75

Section Section

However, the manufacture and in particular the mounting of such alignment plates involve a not inconsiderable expenditure.

It is thus the object of the present invention to develop the component according to the generic clause of claim 1 in such a manner that the electrical terminal members thereof can be reliably and permanently fixed in an exact, predetermined relative position with minimum expenditure.

According to the invention, this object is met by the feature claimed in the characterizing part of claim 1.

- According to the latter, it is provided that a plurality of electrical terminal members is fixed in a predetermined relative position by a plastics body that is injection-molded to said terminal members.
- 95 Fixing of the terminal members in a predetermined relative position by injection-molding of a plastics body to the previously aligned terminal members can be effected in considerably simpler manner than the manufacture and mounting of an alignment plate or the like. Furthermore, terminal members fixed by a molded-on plastics body are fixed in considerably exacter and safer manner than in case of utilization of alignment plates or the like.

With a component designed as claimed, the electrical terminal members can be reliably and permanently fixed in an exact, predetermined relative position with minimum expenditure.

Advantageous developments of the invention are set forth in the dependent claims, the following description and the figures.

The invention will be elucidated hereinafter in more detail with reference to the drawings wherein

115

- Fig. 1 shows a side view of an electrical connector described in more detail hereinafter;
- Fig. 2 shows a front view of the electrical connector shown in Fig. 1;
  - Fig. 3 shows a sectional side view of the electrical connector shown in the preceding figures (section along the line III-III in Fig. 2),

125

- Fig. 4 shows a bottom view of the electrical connector shown in the preceding figures, and
- Fig. 5 shows a conventional electrical connector.

130

135

140

The component with respect to which the invention will be described in more detail hereinafter is an electrical connector. However, it is to be pointed out already here that the special features of the electrical connector described in more detail hereinafter can be applied to other components as well.

The electrical connector illustrated in more detail herein comprises a multiplicity of electrical terminal members to be soldered to the printed circuit board. The special features of the electrical connector described in more detail hereinafter, however, may also be employed with other components connected to the circuit board other than by soldering.

The electrical terminal members to be soldered to the circuit board, in the embodiment illustrated, are SMT contacts designed for surface-mounting of the component on the circuit board. However, the electrical terminal members to be soldered to the circuit board may also be terminal members designed for soldering (reflow soldering, wave soldering etc.) in plated-through holes of the circuit board.

150

175

- 155 It would be conceivable just as well that the electrical terminal members of the components to be soldered to the circuit board are terminal members designed for soldering thereof on the opposite side of the circuit board.
- 160 It is to be pointed out already here that the provision of the special features described hereinafter has very advantageous effects with components in which the electrical terminal members are constituted by SMT contacts; however, positive effects can be achieved also with components the electrical terminal members of which are designed for soldering in accordance with a different method.

The electrical connector illustrated in more detail here in so far corresponds to the electrical connector described initially with reference to Fig. 5.

The connector illustrated in more detail here distinguishes itself in particular in that a plurality of electrical terminal members are fixed in a predetermined relative position by a plastics body that is injection-molded thereto.

This will be described in more detail hereinafter with reference to Figs. 1 to 4.

•

185

190

195

200

210

215

The already mentioned electrical terminal members of the electrical connector concerned bear the reference numeral 12. In the embodiment illustrated, there is provided a total of 25 electrical terminal members. These are designed and arranged such that they can be soldered to a surface contact matrix comprising 5 rows and 5 columns. It should be obvious that both the number and the arrangement of the electrical terminal members and of the associated surface contacts may be different in arbitrary manner.

In addition thereto, the electrical connector contains a housing 11 which, however, in contrast to the housing 1 of the electrical connector according to Fig. 5 does not only accommodate the contact elements necessary for establishing contact with another electrical connector, but also the majority of the electrical terminal members that are exposed in the electrical connector according to Fig. 5; as regards the electrical terminal members 12, it is in essence just the locations provided for soldering to the circuit board that project from the housing.

205 As can be seen in particular from Fig. 3, the housing 11 in the embodiment illustrated consists of two parts, namely a bottom part 111 and a top part 112.

The bottom part 111 and/or the top part 112 of housing 11 or other constituent parts of the electrical connector may be mechanically connected to printed circuit board LP at one or more anchoring points 15. At these anchoring points, the housing parts, for example, can be soldered to the circuit board, with this soldering in case of surface-mounted components, such as the electrical connector illustrated, preferably taking place in accordance with an SMT process as well. Such or other

anchoring of the electrical connector on the circuit board provides the same with a firm hold; moreover, in case of mechanical loads, it cannot be detached from the circuit board as easily as without such anchoring. The anchoring elements may also facilitate that the electrical connector assumes its proper position when the same is mounted on the circuit board.

225

220

. . .

For exact positioning of the electrical connector on the printed circuit board, the embodiment illustrated moreover provides for one or more positioning pins 16 to be inserted into associated openings in the circuit board.

230

235

240

3 also illustrates the contact elements of the Fig. electrical connector provided for connecting the same to another electrical connector; these are designated 13 in Fig. 3. The contact elements 13 are arranged behind insertion openings 113 provided in housing 11; through these insertion openings, the contact elements of the electrical connector to be contacted with the illustrated electrical connector, may be contacted with contact elements 13. As can be seen in particular from Fig. 2, a total of 25 insertion openings 113 is provided in the embodiment illustrated; these are arranged in a matrix of 5 rows and 5 columns. The insertion opening rows extend in horizontal direction and are constituted by insertion openings arranged laterally beside each other; these are designated ER1 to ER5 in the figures. The insertion opening columns extend in vertical direction and are constituted by insertion openings arranged one above the other; these are designated ES1 to ES5 in the figures.

250

245

The contact elements 13 arranged behind the insertion openings 113 are connected to the electrical terminal members 12 or merge with the same. The electrical termi-

255

260

265

270

275

280

285

nal members, or to be more precise, the locations thereof to be soldered to the circuit board are arranged in a matrix of 5 rows and 5 columns as well. This can be seen in particular from Fig. 4. The terminal member rows are designated AR1 to AR5, and the terminal member columns are designated AS1 to AS5. In this regard, the contact elements and terminal members provided at mutually corresponding locations within the matrices are connected to each other. I.e., a contact element provided behind the mth insertion opening column and the nth insertion opening row is connected to the terminal member provided in the mth terminal member column and the nth terminal member row.

As was already pointed out hereinbefore, provisions have to be taken with SMT components, such as the electrical connector illustrated, that the locations of the electrical terminal members to be soldered to the circuit board are coplanar.

In the embodiment illustrated, this is achieved in that the electrical terminal members brought into a corresponding relative position have plastics material injection-molded therearound. Due to this, a common plastics body is formed around the terminal members, through which the terminal members extending through the same are fixed in their relative position taken at the time of the injection molding operation. For the sake of completeness, it is to be pointed out that the locations of the terminal members to be soldered to the circuit board, of course, are not subject to injection-molding; the plastics body injection-molded around the terminal members is arranged and dimensioned such that it does not interfere with the mounting of the electrical component on the circuit board.

Depending on the particular requirements, either all or only specific terminal members may have material injection-molded therearound as described. The terminal members to be subjected to such injection molding may be fixed by a plastics body common to all terminal members or by several individual plastics bodies.

In the embodiment illustrated, the latter possibility is employed. In doing so, the terminal members are subjected to such injection molding in the forms of columns each. This turns out to be particularly advantageous since the terminal members of a terminal member column may be manufactured in common as well: the terminal members arranged in a column each (preferably together with the associated contact elements) may be commonly stamped and formed from one single sheet metal member. The injection molding operation of the commonly manufactured (in the same sequence of operations) turns out to be particularly simple since these may thus be processed further directly after their manufacture.

300

305

310

315

320

325

The terminal members of the electrical connector illustrated are thus fixed in columns by plastics bodies of their own each. These plastics bodies are lamella-like structures designated K1 to K5 in the figures.

Due to the fact that at all times "only" those terminal members are connected via a common plastics body that are manufactured in the same sequence of operations each, and due to the fact that injection molding of plastics material around the terminal members may take place immediately after manufacture thereof, the terminal members can be fixed in their relative position in which they were stamped out. If the terminal members are stamped out such that they take the desired relative position after stamping, the terminal members can be fixed in the desired relative position by the subsequent mold-

350

355

ing of plastics material therearound, without a preceding adjustment.

330 If the terminal members, as in the embodiment illustrated, are fixed in their desired relative positions independently of each other by several separate plastics bodies, it turns out to be expedient if the plastics bodies, preferably at a central location thereof, are provided with structures by means of which the several plastics bodies and thus all terminal members of the electrical connector may be brought into a predetermined relative position.

In the embodiment illustrated, the structures mentioned are formed by vertically extending grooves 14 in plastics bodies K1 to K5. The grooves may receive, by arrangement of the top part 112 of housing 11 thereon, elements provided on the latter, such as e.g. vertically extending intermediate walls, webs, pegs, pins and the like. The plastics bodies thus can be aligned in lateral direction relative to each other.

In particular with very large electrical connectors (having many columns) or other components, it may turn out expedient if the alignment of the plastics bodies as described or in a different manner does not restrict the movability thereof in the direction perpendicular to the circuit board surface. The plastics bodies along with the terminal members extending through the same may then - driven by their own weight - move downwardly to different extents independently of each other and may thus compensate irregularities present in the circuit board.

With a component that is designed as described, it is possible irrespective of the details of the practical realization to reliably and permanently fix the electri-

cal terminal members in an exact, predetermined relative position with minimum expenditure.

characterized in that the terminal members (12) of the terminal member groups each are such terminal members that are manufactured in common.

40

45

- 4. A connector according to any of claims 1 to 3, characterized in that the terminal members (12) of the terminal member groups each are such terminal members that can be connected to the circuit board (LP) at mutually adjacent locations.
- 5. A connector according to any of claims 1 to 4, characterized in that the several plastics bodies

  (K1 to K5) along with the terminal member groups extending through the same are movable relative to each other.
  - 6. A connector according to any of the preceding claims;
- characterized in that the terminal members (12) extending through the respective plastics bodies (K1 to K5) are the sole constituent parts each of the connector to which the plastics bodies are connected.

# JC10 Rec'd PCT/FIU 1 9 FED ZUUZ

1/2

"ANNEXES" of IPER (PCT/IB00/1377)


#### Translation of Amended Claims


#### Claims

- 1. An electrical connector for mounting on a printed circuit board (LP), comprising a multiplicity of 10 electrical terminal members (12) to be connected to said circuit board and being in the form of a matrix including a plurality of rows and columns each, in that several terminal characterized each comprising several terminal members groups, 15 (12) in the form of SMT contacts to be soldered to the circuit board, are fixed in a predetermined relative position independently of each other by plastics bodies (K1 to K5) of their own that are injection-molded thereto, that several plastics bodies 20 (K1 to K5) along with the terminal member groups extending through the same are adapted to be fixed in predetermined relative positions, and in that plastics bodies fixed in a predetermined relative position, along with the terminal member groups extend-25 ing through the same, are movable perpendicularly to the circuit board surface independently of each other.
- 2. A connector according to claim 1, characterized in that the plastics body (K1 to K5) along with the terminal members (12) extending through the same is movable relative to specific or all remaining constituent pars of the connector.
  - 3. A connector according to claim 1 or 2,

#### Abstract

Described is a component for mounting on a circuit board, comprising a multiplicity of electrical terminal members for connection to said circuit board. The component is characterized in that several electrical terminal members are fixed in a predetermined relative position by a plastics body that is injection-molded thereto. The electrical terminal members can thus be permanently and reliably fixed in an exact, predetermined relative position with minimum expenditure.





14 12 AS5 K5-15\_ . K4-AS4 AS3 K3~ ~15 K2~ AS2 16\_ K1-AS1 AR5 AR4 AR3 AR2 AR1

FIG 4




FIG 5

The state of the s raye ruf 3

Docket No.
KSN0026

# **Declaration and Power of Attorney For Patent Application English Language Declaration**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name,

I believe I am the original, first and sole inventor (if only one name is listed below) or an original

the specification of wh	ich	TED CIRCUIT BOARD	
(check one)			
(61.661( 61.6)			
<ul> <li>□ is attached hereto.</li> <li>☑ was filed on February Application Number</li> </ul>	uary 19, 2002 er 10/049,947	as United States Application No	. or PCT International
and was amended	on February 19, 200	(if applicable)	
I hereby state that I had including the claims, a	ave reviewed and ur s amended by any a	nderstand the contents of the above amendment referred to above.	identified specification,
I acknowledge the dut known to me to be n Section 1.56.	y to disclose to the naterial to patentab	United States Patent and Trademar oility as defined in Title 37, Code of	k Office all information f Federal Regulations,
Section 365(b) of any any PCT International listed below and have	foreign application application which de also identified below PCT International amed.	inder Title 35, United States Code, (s) for patent or inventor's certificate esignated at least one country other to, by checking the box, any foreign application having a filing date before	e, or Section 365(a) of than the United States, pplication for patent or
DE 19939584.5	Germany	20 August 1999	
(Number)	(Country)	(Day/Month/Year Filed)	
(Number)	(Country)	(Day/Month/Year Filed)	
,			
(Number)	(Country)	(Day/Month/Year Filed)	

I hereby claim the benefit under application(s) listed below:	35 U.S.C. Section 119(e	) of any United States provisional
(Application Serial No.)	(Filing Date)	
(Application Serial No.)	(Filing Date)	
(Application Serial No.)	(Filing Date)	

I hereby claim the benefit under 35 U. S. C. Section 120 of any United States application(s), or Section 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. Section 112, I acknowledge the duty to disclose to the United States Patent and Trademark Office all information known to me to be material to patentability as defined in Title 37, C. F. R., Section 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application:

PCT/IB00/01377	21 August 2000	Pending		
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)		
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)		
(Application Serial No.)	(Filing Date)	(Status) (patented, pending, abandoned)		

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

9	POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (list name and registration number)  Eric J. Groen, 32,230  Gerard T. Gallagher, 39,679  Daniel Tychonievich, 41,358  Kevin R. Erdman, 33,687  Michael S. Gzybowski, 32,816  John F. Hoffman, 26,280  Anthony Niewyk, 24,871  Nancy G. Tinsley, 37,098  Arthur R. Whale, 18,778
	Send Correspondence to: Eric J. Groen  Baker & Daniels  205 West Jefferson Blyd., Suite 250  South Bend, IN 46601
	Direct Telephone Calls to: (name and telephone number) Eric J. Groen (574)234-4149
160	Full name of sole or first inventor  Johan Vanbesien  Sole or first inventor's signature  Plan Varian  Residence  Meenseweg 464, B-8902 Ieper, Belgium  Citizenship  Belgium  Post Office Address  Meenseweg 464, B-8902 Ieper, Belgium
·	
	Full name of second inventor, if any
	Second inventor's signature Date
	Residence
•	Citizenship
	Post Office Address
	,
l	

PTO/SB/122 (10-01) Approved for use through 10/31/2002. OMB 0651-0035 U.S. Patent and Trademark Office. U.S. DEPARTMENT OF COMMERCE a collection of information unless it displays a valid OMB control number.

Under the Paperwork Reduction Act of 1995, no persons are required to res

# **CHANGE OF CORRESPONDENCE ADDRESS** Application

Address to:

Assistant Commissioner for Patents Washington, D.C. 20231

polic to a conection of information unless i	t displays a valid Olvib control number.
Application Number	10/049,947
Filing Date	February 19, 2002/IA:8/21/00
First Named Inventor	Johan Vanbesien
Art Unit	
Examiner Name	
Attorney Docket Number	KSN0026

Please change the Correto:  Customer Nu  OR  Firm or Individual Name  Address	espondence Address for the above-i umber	dentifie	d ap		2 Lat	ber-Bar Code Jehere EMARK OFFICE	
Address							
City		State			ZIP		
Country							
Telephone		F	ax				
This form cannot be used to change the data associated with a Customer Number. To change the data associated with an existing Customer Number use "Request for Customer Number Data Change" (PTO/SB/124).  I am the:  Applicant/Inventor.  Assignee of record of the entire interest. Statement under 37 CFR 3.73(b) is enclosed. (Form PTO/SB/96).  Attorney or Agent of record.  Registered practitioner named in the application transmittal letter in an application without an executed oath or declaration. See 37 CFR 1.33(a)(1). Registration Number							
Typed or Printed Name Eric J. Groen, Reg. No. 32,230  Signature Signature							
NOTE: Signatures of all the inventors or assignees of record of the entire interest or their representative(s) are required. Submit multiple forms if more than one signature is required, see below*.							

forms are submitted.